

SUBMITTAL

Golden Glow Foil

DESCRIPTION

Golden Glow building insulation is a light density thermal and acoustical fibre glass insulation bonded with thermo-setting resin. This flexible insulation will not stain nor corrode metal studs, rot or sustain fungi or vermin. **Golden Glow** will not shrink nor settle from vibration, exposure, temperature or humidity.

Foil-Faced building insulation is manufactured using an aluminum foil vapor retarder adhered to the fibre glass batt. Tabs or flanges are provided at the edges for stapling or taping to the face or inside of the stud. The foil facing has a vapor transmission (perm) rating of 0.5 or less.

USES

This product is designed for use in residential and commercial, wood or steel stud construction where thermal and acoustical insulation is required in walls, floors and ceilings. **Golden Glow Foil** is easy to install and can be used in both vertical and horizontal applications and in both new and retrofit construction projects.

ADVANTAGES

Golden Glow Foil faced batts have good body and recovery to ensure thermal performance in all applications. Easy to cut with a knife to fit around a variety of surfaces, **Golden Glow Foil** batts have tabs that fold out to tape or staple to the face or to the inside of studs. **Golden Glow Foil** batts are an excellent economical component of any building with long life performance and virtually no maintenance.



LIMITATIONS

Foil facing is adhered with asphalt and should not be left exposed. It should be installed behind, and in substantial contact with the walls and ceilings.

CODES, STANDARDS, RATINGS & LISTINGS

Golden Glow Foil batts comply with ASTM C665, Type III, Class B, and ASTM E 84-98 (Federal specification HH-I-521F has been cancelled and replaced by ASTM C655).

The foil facing has a vapor transmission (perm) rating of 0.05 or less (ASTM E--96-A).

SUBMITTAL

Golden Glow Foil

ESTIMATING, ORDERING & SPECIFYING DATA

Foil Faced Batts (Type III, Class B)				Foil Faced Batts (Type III, Class B)			
R-value	Dimension	PCS/Bag	Sq Ft/bag	R-value	Dimension	PCS/Bag	Sq Ft/bag
R11	3.50" x 15" x 48"	25	125.00	R19	6.25" x 15" x 93"	6	58.13
R11	3.50" x 15" x 93"	11	106.56	R19	6.25" x 23" x 93"	6	89.13
R11	3.50" x 16" x 96"	11	117.33	R30s	8.25" x 15" x 48"	8	40.00
R13	3.50" x 15" x 48"	14	70.00	R30	10" x 15" x 48"	10	50.00
R13	3.50" x 23" x 93"	9	133.69	R30	10" x 16" x 48"	10	53.33
R13	3.50" x 24" x 48"	18	144.00	R30	10" x 23" x 48"	10	76.67
R13	3.50" x 15" x 93"	9	87.19	R30	10" x 24" x 48"	10	80.00
R15s	3.50" x 15" x 93"	6	58.13	R38	12" x 16" x 48"	8	42.67
R19	6.25" x 15" x 48"	15	75.00	R38	12" x 24" x 48"	8	64.00
R19	6.25" x 23" x 48"	15	115.00				

N.B. For skews not shown above, please contact your distributor/agent for details on availability/minimum orders.

SPECIFICATION

When specifying **Golden Glow** state the R-value and the designation "**Foil faced**".

OFI INSULATION FAMILY

Golden Glow Foil Faced Batts are just one member of OFI's "Insulation Family", including **Golden Glow** Kraft unfaced and FSK Faced Batts, Golden Glow Noise Control, QuickPak, OFIVERSATILE ceiling panels, OFICinatile, and OFI Commercial/Industrial Insulations.

SUBMITTED TO:	_____
SUBMITTED BY:	_____
DATE:	_____
JOB REFERENCE:	_____
JOB NAME:	_____



Ottawa Fibre Inc.

For more information: Telephone: (613) 247-7116 Facsimile: (613) 736-7281