

SUBMITTAL

Golden Glow Kraft

DESCRIPTION

Golden Glow Kraft Faced building insulation is a light density thermal and acoustical fibre glass insulation bonded with thermo-setting resin. This flexible insulation will not stain or corrode metal studs, rot or sustain fungi or vermin.

Golden Glow will not shrink or settle from exposure, vibration, temperature or humidity.

The kraft facing is laminated to the insulation and serves as a vapor barrier/retarder. *Kraft facings are combustible and should not be left exposed.* (Application and safety data are clearly indicated on the package).

Golden Glow Kraft faced batts are manufactured in a variety of R-values.

The higher the R-value, the greater the insulating power. Compressing insulation below its design thickness reduces thermal performance. Choose the proper thickness for the design.

USES

Golden Glow Kraft faced batts are designed for friction fit applications in wood and steel stud construction in walls, ceilings and floors. They can be used in new construction or renovation in both residential and commercial applications. **Golden Glow Kraft** is easy to install and can be used in both horizontal and vertical applications, as it will not shrink, settle or sag from vibration.

ADVANTAGES

Golden Glow Kraft has good body and recovery to ensure good performance in walls, ceilings and floors. **Golden Glow Kraft** is easy to cut with a knife, fit between studs and form around a variety of surfaces. The kraft paper facing has tabs that fold out and over



studs to allow mechanical fastening.

Golden Glow Kraft is an excellent economical component of any building system with long life performance and virtually no maintenance.

CODES, STANDARDS, RATINGS & LISTINGS

Kraft paper is flammable and therefore not rated according to ASTM E-84. Unfaced batts are tested according to ASTM E-84 and meet the 25/50 standard. Unfaced batts are considered non-combustible according to ASTM E-136. Meets ASTM C665 Type 2 Class C. ASTM E 84-98 (Federal specification HH-I-521F has been cancelled and replaced by ASTM C655). **Golden Glow**, exclusive of facings is UL listed.

LIMITATIONS

Local building codes.

SUBMITTAL

Golden Glow Kraft

ESTIMATING, ORDERING & SPECIFYING DATA

"S" denotes high density/ * denotes minimum order may apply

Kraft Faced Batts (Type 2, Class C)							
R-value	Dimension	PCS/Bag	Sq Ft/bag	R-value	Dimension	PCS/Bag	Sq Ft/bag
R11	3.50"x11.25"x93"	22	159.84	R19	6.25"x16"x48"	15	80.00
*R11	3.50"x15"x48"	25	125.00	*R19	6.25"x16"x93"	6	62.00
R11	3.50"x15"x93"	11	106.56	R19	6.25"x16"x96"	6	64.00
R11	3.50"x15"x105"	12	131.25	*R19	6.25"x23"x48"	15	115.00
*R11	3.50"x16"x96"	11	117.33	R19	6.25"x23"x94"	6	90.08
R11	3.50"x23"x94"	11	165.15	R19	6.25"x24"x48"	15	120.00
*R11	3.50"x24"x48"	25	200.00	*R21s	5.50"x15"x47"	11	53.85
R13	3.50"x11.25"x93"	14	101.72	*R26	9"x24"x48"	11	88.00
R13	3.50"x15"x48"	14	70.00	R30	10"x15"x48"	10	50.00
R13	3.50"x15"x94"	9	88.13	R30	10"x16"x48"	10	53.33
R13	3.50"x15"x106"	9	99.38	R30	10"x23"x48"	10	76.67
*R13	3.50"x23"x94"	9	135.13	R30	10"x24"x48"	10	80.00
*R13	3.50"x24"x48"	14	112.00	R30s	8.25"x15"x48"	8	40.00
*R15s	3.50"x15"x93"	6	58.13	*R38s	8.25"x23"x48"	8	61.33
R19	6.25"x11.25"x93"	12	87.19	R38	12"x15"x48"	8	40.00
R19	6.25"x15"x48"	15	75.00	R38	12"x16"x48"	8	42.67
R19	6.25"x15"x94"	6	58.75	*R38	12"x23"x48"	8	61.33
*R19	6.25"x15"x96"	6	60.00	R38	12"x24"x48"	8	64.00
R19	6.25"x15"x106"	6	66.25	*R38s	10.25"x15"x48"	6	30.00

SPECIFICATION

When specifying **Golden Glow** state the R-value and the designation "**Kraft-Faced batts**".

OFI INSULATION FAMILY

Golden Glow Kraft Faced Batts are just one member of OFI's "Insulation Family", including **Golden Glow** Unfaced, FSK and Foil Faced Batts, Golden Glow Noise Control, QuickPak, OFIVERSATILE Commercial and Residential Ceiling Tiles, and OFI Commercial/Industrial Insulations.

SUBMITTED TO:	_____
SUBMITTED BY:	_____
DATE:	_____
JOB REFERENCE:	_____
JOB NAME:	_____



Ottawa Fibre Inc.

For more information: Telephone: (613) 247-7116 Facsimile: (613) 736-7281