

SUBMITTAL

Golden Glow Unfaced

DESCRIPTION

Golden Glow Unfaced building insulation is a light density thermal and acoustical fibre glass insulation bonded with a thermo-setting resin. This flexible insulation will not stain or corrode metal studs, rot or sustain fungi or vermin. **Golden Glow** will not shrink or settle from exposure, vibration, temperature or humidity. Where vapor control is required, a separated code accepted poly vapor barrier can be used with this product. **Golden Glow** is manufactured in a variety of R-values. **The higher the R-value, the greater the insulating power.** Compressing insulation below its design thickness reduces thermal performance. Choose the proper thickness for the design.

USES

Golden Glow Unfaced batts are designed for friction fit applications in wood and steel stud construction in walls, ceilings and floors. They can be used in new construction, or renovation in both residential and commercial applications. **Golden Glow** is easy to install and can be used in both horizontal and vertical applications, as it will not shrink, settle or sag from vibration.

ADVANTAGES

Golden Glow has good body and recovery to ensure good performance in walls, ceilings and floors. **Golden Glow** is easy to cut with a knife, fit between studs, and form around a variety of surfaces. **Golden Glow** is an excellent economical component of any building system with long life performance and virtually no maintenance.



CODES, STANDARDS, RATINGS & LISTINGS

Unfaced batts are tested to ASTM E-84 and meet the 25/50 standard. Unfaced batts are considered non-combustible according to ASTM E-136.

Meets ASTM C665 Type 1. ASTM E 84-98 (Federal specification HH-I-521F has been cancelled and replaced by ASTM C655).

Golden Glow, exclusive of facings, is UL & MEA listed.

LIMITS

Local building codes.

N.B. Golden Glow Unfaced batts are non-combustible, but kraft or poly vapor barriers are and should not be left exposed.

SUBMITTAL

Golden Glow Unfaced

ESTIMATING, ORDERING & SPECIFYING DATA

"S" denotes high density/ * denotes minimum order may apply

Unfaced Batts (Type 1, Class C)					Unfaced Batts (Type 1, Class C)				
R-value	Dimension	PCS/Bag	Sq Ft/bag		R-value	Dimension	PCS/Bag	Sq Ft/bag	
R11	3.50" x 11.25" x 93"	22	159.84		R19	6.25" x 24" x 96"	6	96.00	
R11	3.50" x 15" x 48"	25	125.00		*R21s	5.50" x 15" x 47"	11	53.85	
R11	3.50" x 15" x 93"	11	106.56		*R21s	5.50" x 15" x 48"	11	55.00	
R11	3.50" x 15" x 105"	12	131.25		R30	10" x 12" x 48"	20	80.00	
R11	3.50" x 16" x 48"	25	133.33		R30	10" x 15" x 48"	10	50.00	
*R11	3.50" x 16" x 93"	11	113.67		R30	10" x 16" x 48"	10	53.33	
R11	3.50" x 16" x 96"	11	117.33		*R30	10" x 23" x 48"	10	76.67	
*R11	3.50" x 23" x 48"	25	191.67		R30	10" x 24" x 48"	10	80.00	
*R11	3.50" x 23" x 93"	11	163.40		*R30s	8.25" x 15" x 48"	8	40.00	
*R11	3.50" x 24" x 48"	25	200.00		*R38	12" x 15" x 48"	8	40.00	
*R11	3.50" x 24" x 93"	11	170.50		R38	12" x 16" x 48"	8	42.67	
*R11	3.50" x 24" x 96"	11	176.00		R38	12" x 24" x 48"	8	64.00	
R13	3.50" x 11.25" x 93"	14	101.72		*R38s	10.25" x 15" x 48"	6	30.00	
R13	3.50" x 15" x 48"	14	70.00		*R38s	10.25" x 23" x 48"	6	46.00	
R13	3.50" x 15" x 93"	7	67.81		*R38s	10.25" x 24" x 48"	6	48.00	
R13	3.50" x 15" x 105"	9	98.44						
*R13	3.50" x 16" x 48"	14	74.67						
*R15s	3.50" x 15" x 93"	6	58.13						
R19	6.25" x 11.25" x 93"	12	87.19						
R19	6.25" x 15" x 47"	15	73.44						
R19	6.25" x 15" x 48"	15	75.00						
R19	6.25" x 15" x 93"	6	58.13						
R19	6.25" x 16" x 48"	15	80.00						
*R19	6.25" x 16" x 93"	6	62.00						
R19	6.25" x 16" x 96"	6	64.00						
R19	6.25" x 23" x 48"	15	115.00						
R19	6.25" x 23" x 93"	6	89.13						
R19	6.25" x 24" x 48"	15	120.00						

Noise Control Batts – Unfaced (Type 1, Class C)				
R-value	Dimension	PCS/Bag	Sq Ft/bag	
R8 N/C	16" x 96" x 2.75"	16	170.67	
R8 N/C	16" x 48" x 2.75"	32	170.67	
R8 N/C	24" x 96" x 2.75"	16	256.00	
R8 N/C	24" x 48" x 2.75"	32	256.00	
R11 N/C	4.0" x 16" x 48"	25	133.33	
R11 N/C	4.0" x 16" x 96"	11	117.33	
R11 N/C	4.00" x 24" x 48"	25	200.00	
R11 N/C	4.00" x 24" x 96"	11	176.00	

SPECIFICATION

When specifying Golden Glow state the R-value and the designation "Unfaced".

SUBMITTED TO:	_____
SUBMITTED BY:	_____
DATE:	_____
JOB REFERENCE:	_____
JOB NAME:	_____

OFI INSULATION FAMILY

Golden Glow Unfaced Batts are just one member of OFI's "Insulation Family", including Golden Glow Kraft and Foil Faced Batts, Golden Glow Noise Control, QuickPak, OFIVERSATILE Commercial and Residential Ceiling Tiles, and OFI Commercial/Industrial Insulations.



Ottawa Fibre Inc.

For more information: Telephone: (613) 247-7116 Facsimile: (613) 736-7281