


MAGNUM R-100 All Purpose

Ready Mix Joint Compound

<p>Description:</p> <p>Magnum All Purpose Ready Mix Joint Compound is a professional quality, vinyl based, factory premixed formulation. It is designed for embedding drywall tape, spotting fasteners, finishing joints and cornerbead, and the application of simple textures. It can also be used for patching cracks in plaster walls.</p> <p>Advantages:</p> <ul style="list-style-type: none">• Less air than other compounds• Factory premixed• Excellent adhesion• Low shrinkage• More open time/Less tool drag	<p>Site Requirements and Storage:</p> <ul style="list-style-type: none">• Maintain 55° F building working temperature until dry• Protect from freezing, extreme heat, direct sunlight• Rotate stock each nine months <p>Coverage:</p> <p>125-150 lbs. covers 1000 sq ft of gypsum panel</p> <p>Available:</p> <ul style="list-style-type: none">• 50 lb cartons (22.7kg)• 62 lb pail (28.1kg)• 13 lb pail (1 gallon) <p>Decoration:</p> <p>Final wallboard finish should comply with the Five Levels of Gypsum Board Finish approved by the Gypsum Association, The Painting and Decorating Contractors of America, the Drywall Finishing Council, and The Association of Wall and Ceiling Industries.</p>	<p>Standards:</p> <p>Meets ASTM C475-89</p> <p>Precautions:</p> <p>May contain mica, talc, plaster, limestone, perlite, clay and latex. Wet sanding is advisable to avoid creating dust. When dry sanding, use of a dust collector, eye protection, and a respirator approved by NIOSH to remove dust is advisable. Must not be taken internally. Keep Out Of Reach Of Children.</p> <p>Ingredient Information: 913-888-0882</p> <p></p> <p>P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882</p>
---	--	--